

## Turbine ventilation specifications

Unit	Size (mm)	Material	Extraction rate	Height (mm)	Width (mm)	Length (mm)	Packed weight (kg)
Whirlybird	300	Aluminium	924m <sup>3</sup> /hr	460	475	525	2.7
	350	Aluminium	1155m <sup>3</sup> /hr	545	490	575	3
GT-12	300	Galvanised	924m <sup>3</sup> /hr	460	475	525	6
Twister	500	Galvanised	4695m <sup>3</sup> /hr	620	730	730	21.5
		Aluminium	4695m <sup>3</sup> /hr	620	730	730	16.5
	610	Galvanised	6150m <sup>3</sup> /hr	620	800	800	19.5
		Aluminium	6150m <sup>3</sup> /hr	620	800	800	17
LP Vent	500	Aluminium	3770m <sup>3</sup> /hr	535	630	630	6.4
	600	Aluminium	5395m <sup>3</sup> /hr	620	755	755	8.8
SupaVent	250	Polycarbonate	1229m <sup>3</sup> /hr	510	345	345	2.6
SewerVent	150	Polycarbonate	488m <sup>3</sup> /hr	240	240	240	1.1
GP Vent	130	Polycarbonate	68m <sup>3</sup> /hr	110	210	210	0.6
Hurricane	900	Aluminium	10000 - 12000m <sup>3</sup> /hr	936	1110	1130	24.1